inverELITE V4

WORLD'S MOST EFFICIENT.
WORLD'S QUIETEST.
WORLD CLASS INNOVATION.

2027 MODEL
NEW
& IMPROVED

inverELITE V4 pool heater is the world's most efficient and quietest heat pump. The revolutionary 3-directional airflow ensures almost silent operation and enhanced efficiency. Engineered with installation support features such as plug & play technology, wi-fi, and quick connectivity, the inverELITE V4 sets a new standard in performance and innovation. This unit delivers unmatched pool heating excellence.



Revolutionary 3-Directional Airflow
3D triple-directional airflow minimises installation requirements and enhances efficiency

Triple Layered Sound Insulation
Delivering a 30% reduction in operating noise, it achieves a world breaking decibel rating for heat pump technology

Commercial Grade Centrifugal Fan
The compressor fan is designed with angular blades to capture surplus surrounding air and boost overall efficiency

Twin Rotary Compressor
inverELITE V4 delivers the fastest heat-up times, getting your pool ready quicker than ever

The Most Advanced Heat Pump
This meticulously designed heat pump achieves a groundbreaking COP of 24 to maximize your comfort while minimising your energy use

Plug & Play
Plug & Play installation simplicity for 10kW, 12kW and 15kW

MANUFACTURER'S WARRANT 25 YEARS ON TITANIUM HEAT EXCHANGE
MANUFACTURER'S WARRANT 15 YEARS ON COMPRESSOR
MANUFACTURER'S WARRANT 7 YEARS ON ALL PARTS
1 YEAR LABOUR WARRANTY

madimack Powered by invermac TECHNOLOGY

Model Name	Elite V4 - 10kW	Elite V4 - 12kW	Elite V4 - 15kW	Elite V4 - 17kW	Elite V4 - 19kW
PERFORMANCE CONDITION: Air 27°C/ Water 27°C/ Humid. 80%					
Heating Capacity (kW)	10.2	12	15.0	17.5	19.5
COP Range	19.5~7.8	19.7~8.1	24-8.7	20.4~8.1	20~7.8
PERFORMANCE CONDITION: Air 15°C / Water 26°C / Humid. 70%					
Heating Capacity (kW)	7.0	8.1	9.8	12.0	13.0
COP Range	7.9~5.6	8.1~5.7	9.2~6.1	9.0~5.8	7.9~5.5
PERFORMANCE CONDITION: Air 35°C / Water 28°C / Humid. 80%					
Cooling Capacity (kW)	4.8	5.5	6.7	9.4	10.8
TECHNICAL SPECIFICATIONS					
Temperature set point range (°C)	5°C~40°C				
Operating air temperature (°C)	-20°C~43°C				
Compressor	Twin-Rotary Mitsubishi DC Compressor				
Casing	Aluminum Alloy Casing				
Power supply	230V/ 1Ph/ 50/60 Hz				
Electrical connection	10A Plug (3×1.5 mm^2)	10A Plug (3×1.5 mm^2)	10A Plug (3×1.5 mm^2)	Hardwired (3×2.5 mm^2)	Hardwired (3×2.5 mm^2)
Power cord (mm^2)	3×1.5	3×1.5	3×1.5	3×2.5	3×2.5
Rated input power (kW)	0.16~1.35	0.18-1.53	0.23-1.91	0.27~2.22	0.31~2.55
Rated input current (A)	0.70~5.87	0.78~6.65	1.0~8.30	1.17~9.65	1.35~11.09
Maximum input current (A)	9	10	10.0	16.0	16.5
Breaker Rated Current (A)	15	15	15	20	20
Sound level at 50% 1m dB(A)	36.4	36.5	38.4	40.3	40.5
Sound level at 1m dB(A)	36.0~41.8	36.0~42.5	36.3~43.9	37.2~45.5	37.5~46.0
Sound level at 10m dB(A)	16.0~21.8	16.0~22.5	16.3~23.9	17.3~25.5	17.5~26.0
Advised water flow (L/min) ± 20%	51	51	59	84	100
Water Pressure Drop (kPA)	4	4	5	6	7
Net Weight (kg)	83	83	83	90	94
Gross Weight (kg)	92	92	92	100	104
Net dimension LxWxH (mm)	936×494×655	936×494×655	936×494×655	1036×494×655	1036×494×655
Packaging dimension LxWxH (mm)	1005×550×685	1005×550×685	1005×550×685	1105×550×685	1105×550×685
Gas	R~32				
Water connection (mm)	40 mm				

Model Name	Elite V4 - 23kW	Elite V4 - 28kW	Elite V4 - 34kW	Elite V4 - 42kW
PERFORMANCE CONDITION: Air 27°C/ Water 27°C/ Humid. 80%				
Heating Capacity (kW)	23.0	28.0	34.0	42.0
COP Range	23.0~8.2	20~8.0	20~7.8	18.9~7.8
PERFORMANCE CONDITION: Air 15°C / Water 26°C / Humid. 70%				
Heating Capacity (kW)	15.0	19.3	23.5	30.0
COP Range	9.6~6	8.9~5.7	8.0~5.7	7.8~5.5
PERFORMANCE CONDITION: Air 35°C / Water 28°C / Humid. 80%				
Cooling Capacity (kW)	11.9	13.5	15.4	20.0
TECHNICAL SPECIFICATIONS				
Temperature set point range (°C)	5°C~40°C			
Operating air temperature (°C)	-20°C~43°C			
Compressor	Twin-Rotary Mitsubishi DC Compressor			
Casing	Aluminum Alloy Casing			
Power supply	230V/ 1Ph/ 50/60 Hz			400V/ 3Ph/ 50/60 Hz
Electrical connection	Hardwired (3×4.0 mm^2)	Hardwired (3×4.0 mm^2)	Hardwired (3×4.0 mm^2)	Hardwired (5×2.5 mm^2)
Power cord (mm^2)	3×4.0	3×4.0	3×4.0	5×2.5
Rated input power (kW)	0.33~2.73	0.44~3.64	0.53~4.43	0.71~5.88
Rated input current (A)	1.43~11.87	1.91~15.83	2.30~19.26	1.03~8.52
Maximum input current (A)	18.5	20.5	24	12.5
Breaker Rated Current (A)	25	25	30	15
Sound level at 50% 1m dB(A)	41.0	41.2	43.0	43.6
Sound level at 1m dB(A)	37.6~46.8	37.9~48.2	38.2~48.7	38.8~49.3
Sound level at 10m dB(A)	17.6~26.8	17.9~28.2	18.2~28.7	18.8~29.3
Advised water flow (L/min) ± 20%	125	150	183	250
Water Pressure Drop (kPA)	8	12	16	22
Net Weight (kg)	100	125	154	186
Gross Weight (kg)	112	148	181	216
Net dimension LxWxH (mm)	1104×494×757	1129×504×945	1310×514×945	1405×514×1070
Packaging dimension LxWxH (mm)	1175×550×785	1198×560×985	1380×560×985	1475×560×1105
Gas	R~32			
Water connection (mm)	40 mm			

* The data above is only for reference. For specific data, please refer to the nameplate on the unit. Acoustic data is to TuV international testing conditions, site conditions may differ.

PRIORITISING SUSTAINABLE LIVING

The Madimack Manufacturer Warranty is available on eligible purchases through Madimack Authorised Dealers and Certified Online Dealers. All Madimack products also include guarantees under the Australian Consumer Law.

madimack